



827 S 7th St
 Kansas City, KS 66105
 Main Tel. (833) 653-8100

Specification #2389, Reference 3600 VAC

Customer	Stock Vacuum	Quotation #	2389
Reference	3600 VAC	Date	22-Jul-2020

ITEM	DESCRIPTION	QTY
CHASSIS-FLOWMARK SUPPLIED	Chassis- TBD	1
IV-AL-36	3600 US Gallons Aluminum Vacuum Tank - 3600 total US gallons - single compartment tank - 1/4" barrel - 3/8" heads - reinforced sills with composite isolation boards - 12" primary shut off with 3" plumbing - 20" top manway - 20" rear cleanout - steps at top manway - full head anti-surge baffles - interior ring stiffeners as required - full length aluminum hose trays with diamond plate protector - 4" rear load line with 4" TTMA flange and stainless deflector - 6" discharge with 6" TTMA flange - (2) rear hose hooks - (3) 5" site eyes - LED light kit with S/T/T, (2) work lights, clearance and DOT triple lights - 10 year, no-leak tank warranty	1
IV-PU-NVE866F	Vacuum Pump - NVE866 MaxPak - fan cooled, 520cfm vane pump - air shift PTO for manual transmissions - frame mount NVE secondary shut off - frame mount NVE oil catch muffler - pump stand, gearbox, driveshaft - includes 3in brass lever valve, adapter and dust cap on inlet - includes 4in brass lever valve, adapter and dust cap on discharge - standard pumper bumper	1

Optional Equipment Not Included in Total Price Above		
IV-OPTION-V1	Valve Option - Upgrade inlet valve to 4in, with aluminum cam lock adapter and tethered dust cap	1
IV-OPTION-V2	Valve Option - Upgrade discharge valve to 6in, with aluminum cam lock adapter and tethered dust cap	1
IV-OPTION-36CAB	Toolbox - 36in, 48in or 60in frame mount toolbox - double barn door, smooth aluminum	1
IV-OPTION-806(b)	Garnett Gauge - Add Garnett 802(b)i tank level gauge - In cab or external remote display	1
IV-TO-2C	2 Compartment Tank - 2 compartment tank (/) - 4" top fill, 2" top vent - 2" bottom pump feed	1
IV-TO-36	Tank Option - 36" rear manway in place of 20" - aluminum neck - black painted steel lid	1
IV-TO-HOIST	Tank Option - front hoist, includes hoist brackets, rear hinge, frame brackets for hose trays	1
IV-TO-DOOR	Tank Option - rear door, includes top cylinder, gasket, door, turn buckle closures	1

Specification #2389, Reference 3600 VAC

IV-OPTION-HYD	Hydraulic Install <ul style="list-style-type: none">- hydraulic pump, reservoir, 2 spool valve for hoist and door- front hoist ram- rear opening door rams- air shift PTO for manual transmissions	1
---------------	--	---