



827 S 7th St  
 Kansas City, KS 66105  
 Main Tel. (833) 653-8100

## Specification #2390, Reference 4200 Vac

<b>Customer</b>	Stock Vacuum	<b>Quotation #</b>	<b>2390</b>
<b>Reference</b>	4200 Vac	<b>Date</b>	22-Jul-2020

ITEM	DESCRIPTION	QTY
CHASSIS-FLOWMARK SUPPLIED	<b>Chassis- TBD</b>	1
IV-AL-42	<b>4200 US Gallons Aluminum Vacuum Tank</b> - 4200 total US gallons - single compartment tank - 1/4in barrel - 3/8in heads - reinforced sills with composite isolation boards - 12in primary shut off with 3in plumbing - 20in top manway - 20in rear cleanout - steps at top manway - full head anti-surge baffles - interior ring stiffeners as required - full length aluminum hose trays with diamond plate protector - 4in rear load line with 4in TTMA flange and stainless deflector - 6in discharge with 6in TTMA flange - (2) rear hose hooks - (3) 5in site eyes - LED light kit with S/T/T, (2) work lights, clearance and DOT triple lights - 10 year, no-leak tank warranty	1
IV-PU-NVE866F	<b>Vacuum Pump</b> - NVE866 MaxPak - fan cooled, 520cfm vane pump - air shift PTO for manual transmissions - frame mount NVE secondary shut off - frame mount NVE oil catch muffler - pump stand, gearbox, driveshaft - includes 3in brass lever valve, adapter and dust cap on inlet - includes 4in brass lever valve, adapter and dust cap on discharge - standard pumper bumper	1

Optional Equipment Not Included in Total Price Above		
IV-OPTION-V1	<b>Valve Option</b> - Upgrade inlet valve to 4in, with aluminum cam lock adapter and tethered dust cap	1
IV-OPTION-V2	<b>Valve Option</b> - Upgrade discharge valve to 6in, with aluminum cam lock adapter and tethered dust cap	1
IV-OPTION-36CAB	<b>Toolbox</b> - 36in, 48in or 60in frame mount toolbox - double barn door, smooth aluminum	1
IV-OPTION-806(b)	<b>Garnett Gauge</b> - Add Garnett 802(b)i tank level gauge - In cab or external remote display	1
IV-TO-2C	<b>2 Compartment Tank</b> - 2 compartment tank (/) - 4" top fill, 2" top vent - 2" bottom pump feed	1
IV-TO-36	<b>Tank Option</b> - 36" rear manway in place of 20" - aluminum neck - black painted steel lid	1
IV-TO-HOIST	<b>Tank Option</b> - front hoist, includes hoist brackets, rear hinge, frame brackets for hose trays	1
IV-TO-DOOR	<b>Tank Option</b> - rear door, includes top cylinder, gasket, door, turn buckle closures	1

## Specification #2390, Reference 4200 Vac

IV-OPTION-HYD	<b>Hydraulic Install</b> <ul style="list-style-type: none"><li>- hydraulic pump, reservoir, 2 spool valve for hoist and door</li><li>- front hoist ram</li><li>- rear opening door rams</li><li>- air shift PTO for manual transmissions</li></ul>	1
---------------	--	---