

1000 - 2500 GALLON VACUUM TRUCKS



Chassis:

Ford	Peterbilt	Isuzu
RAM	International	Hino
Kenworth	Freightliner	Mack

Tank:

Aluminum tanks

Configuration:

PTO driven vacuum pump with auto RPM increase, 3" inlet, 4" discharge



STANDARD FEATURES:

Pump

230 cfm, PTO driven vacuum pump with vacuum and pressure modes, primary and secondary shut offs

Inlets

Single rear 4" (3" under 2000 gal) load line, with riser and deflector with 3" brass valve, adapter and dust cap

Discharge

6" rear discharge line (4" under 2000 gal) with 4" brass valve, adapter and dust cap

Hose trays

Aluminum hose trays with heavy duty outriggers, hose protector on tank sides, and rear hose hooks

Manways

20" top manway and 20" rear manway for easy access to tank cleaning (20" combo manway/primary on 2000 and under)

Site eyes

Three 5" site eyes located on rear head

Controls

In cab control for PTO engagement and worklights

Work Lights

2 LED work lights, 1 at each corner

Bumper

Heavy duty steel rear bumper

Cabinets

Aluminum double door tool cabinets available in 36", 48" or 60"

COMMONLY REQUESTED OPTIONS

- 350 - 500 cfm pumps
- 4" inlet valve
- 6" discharge valve
- Heat Options
- Extra Inlet
- 2 compartment tank
- Hoist & door options
- DOT 407 certification

