

3600 - 5500 GALLON VACUUM TRUCKS



Chassis:

Kenworth	Freightliner
Peterbilt	Hino
International	Mack

Tank:

Aluminum tanks

Configuration:

PTO driven vacuum pump with auto RPM increase, 3" inlet, 4" discharge

STANDARD FEATURES:

Pump

350 cfm, PTO driven vacuum pump with vacuum and pressure modes, primary and secondary shut offs

Inlets

Single rear 4" load line, with riser and deflector with 3" brass valve, adapter and dust cap

Discharge

6" rear discharge line with 4" brass valve, adapter and dust cap

Hose trays

Aluminum hose trays with heavy duty outriggers, hose protector on tank sides, and rear hose hooks

Manways

20" top manway and 20" rear manway for easy access to tank cleaning

Site eyes

Three 5" site eyes located on rear head

Controls

In cab control for PTO engagement and worklights

Work Lights

2 LED work lights, 1 at each corner

Bumper

Heavy duty steel rear bumper

Cabinets

Aluminum double door tool cabinets available in 36", 48" or 60"

COMMONLY REQUESTED OPTIONS

350 - 500 cfm pumps

500+ cfm blowers

4" inlet valve

6" discharge valve

Heat Options

Extra Inlet

2 compartment

tank with jetter

Hoist & door options

DOT 407 certification

