



MHC Kenworth 0997
1524 N. CORRINGTON

SKYMARK TANK #7

Kansas City, Missouri United States 64120

Phone:

Phone: (701) 361-8160

Fax:

Fax:

Email:

Contact Email:

Prepared for: Default Contact

Vehicle Summary

Unit		Chassis	
Model:	T370 SERIES	Fr Axle Load (lbs):	20000
Type:	CONVENTIONAL	Rr Axle Load (lbs)	40000
Description:	FULL TRUCK	G.C.W. (lbs):	60000
	Spec 7 HFA 1-1-18	Road Conditions:	
	2020MY	Class A (Highway)	90
Application	Local pickup & delivery.	Class B (Hwy/Mtn)	10
Intended Serv.:	Vehicles which haul	Class C (Off-Hwy)	00
Commodity:	Liquid petroleum products	Class D (Off-Road)	00
		Maximum Grade:	6
Body	Tank	Wheelbase (in):	230
Type:	20.0	Overhang (in):	107
Length (ft):	12.0	Fr Axle to BOC (in):	68
Height (ft):	4000	Cab to Axle (in):	162
Max Laden Weight (lbs):		Cab to EOF (in):	269
		Overall Comb. Length (in):	377
Trailer		Special Req.	
No. of Trailer Axles:	0	U.S. Domestic Registry, 50-State	
Type:			
Length (ft):	0.0		
Height (ft):	0.0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	120		
Width (in):	102		
Height (ft):	15.0		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/3/2019 12:56:00 PM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q00099293
Prepared by:	ID: mkilgor		Version Number:	41.20



MHC Kenworth O997
1524 N. CORRINGTON

SKYMARK TANK #7

Kansas City, Missouri United States 64120

Phone:

Phone: (701) 361-8160

Fax:

Fax:

Email:

Contact Email:

Prepared for: Default Contact

Data	Code	Description	Weight
Model			
0000370	O	T370 SERIES CONVENTIONAL Electric Door locks LH/RH; Ignition & doors keyed alike; Single electric horn; Single-piece windshield; Electric windshield wipers, 2-speed plus intermittent; Electric windshield washers; Steering wheel 18in. 4-spoke; Glovebox door with locking latch; Dash-mounted cruise control with switches; Turn signal switch with column-mounted dimmer; Standard dash panels include gray w/ burl wood accents; Slate Gray interior primary color; Dark Slate Gray seat color; Floor mat; Inside sunvisor, LH/RH; Door courtesy lights; Under-dash center console with 1 cup holder, 1 ashtray & 1 lighter.	9,642
0070006	O	T370 Class 7: medium-duty Conventional.	0
0080050	O	CARB Idle Emissions Reduction Feature for PX-7 and PX-9	0
0090022	O	Medium-duty 18k/20k Heavy Front Axle.	0
0091070	O	Liquid petroleum products	0
0093005	O	Local pickup & delivery. Vehicles which haul freight, typically operating within a 100-mile radius, on public streets & highways, & other paved surfaces, including limited Class C roads. Includes package & freight delivery, as well as fuel oil or petroleum distribution, etc. Road usage: minimum 3% Class B, do not code for Class D.	0
0095110	O	Tank	0
0098025	O	U.S. Domestic Registry, 50-State	0

Engine & Equipment

0129546	O	PACCAR PX-9 350 2017 350@2000 321@2200 1150@1400 Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing. N09200 N205 68...Standard Maximum Speed Limit [LSL] N09220 N207 0...Expiration Distance N09260 P14 68...Maximum Accelerator Pedal Vehicle Speed N09300 P19 68...Maximum Cruise Speed N09360 N203 252..Reserve Speed Function Reset Distance N09380 N202 0...Maximum Cycle Distance N09400 N206 10...Maximum Active Distance N09420 N201 0...Reserve Speed Limit Offset N09440 P11 YES..Engine Protection Shutdown N09460 P06 NO...Gear Down Protection N09480 P26 1000.Max PTO Speed	555
---------	---	---	-----

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/3/2019 12:56:00 PM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q00099293
Prepared by:	ID: mkilgor		Version Number:	41.20



Data	Code	Description	Weight
		N09500 P02 NO...Cruise Control Auto Resume	
		N09520 P04 NO...Auto Engine Brake in Cruise	
		N09540 N209 0...Expiration Distance	
		N09560 P520 YES..Enable Idle Shutdown Park Brake Set	
		N09580 P32 5...Timer Setting	
		N09600 P233 YES..Enable Impending Shutdown Warning	
		N09620 P234 60...Timer For Impending Shutdown Warning	
		N09640 P516 35...Engine Load Threshold	
		N09680 P33 NO...Idle Shutdown Manual Override	
		N09720 P230 YES..Enable Hot Ambient Automatic Override	
		N09740 P46 40...Low Ambient Temperature Threshold	
		N09760 P56 60...Intermediate Ambient Temperature Threshold	
		N09780 P47 80...High Ambient Temperature Threshold	
1000158	O	Prospector Version 43.0 Replaces 42.1	0
1000684	O	Effective VSL Setting NA	0
1000858	O	Engine Idle Shutdown Timer Disabled	0
1000859	O	Enable EIST Ambient Temp Override	0
1000891	O	Eff EIST NA Expiration Miles Use only with MX and Cummins engines	0
1002060	S	Air compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.	0
1031130	S	Air Cleaner: Dry-type firewall mounted w/filter restriction indicator.	0
1105231	O	Fan Hub: Horton On/Off for PX-9 or ISLG	0
1121200	S	Cooling module: 1000 square inches T170/T270/T370/T470. Includes metal surge tank on T170/T270/T370.	0
1247194	O	Exhaust:2017 EPA RH Under Cab DPF/SCR For PX-9 w/ Single Vertical RH Side of Cab Tailpipe.	215
1290130	O	Tailpipe: 5 in. single 30 in. 45 degree curved.	0
1321145	O	Fuel Filter:Fleetguard FS1003 Fuel/Water Separator for PX-9	0
1321200	O	Run Aid:None *For Fuel Filter	0
1321305	O	Start Aid:12V Heat *For Fuel Filter	1
1504006	O	Block heater, PACCAR 1750 watt 120V for PX-6 and PX-7, 1000 watt for PX-8 and PX-9 or ISL9 engines .	2
1816260	S	Alternator: PACCAR 160 amp, brush type	0
1821210	O	Batteries: 3 PACCAR GP31 threaded post (700-730) 2100-2190 CCA dual purpose.	57
1836100	S	Starter: PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/3/2019 12:56:00 PM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q00099293
Prepared by:	ID: mkilgor		Version Number:	41.20



Data	Code	Description	Weight
1900082	O	Multi-function engine connector for body builder interface for Cummins.	0
1900976	O	Body Builder Control Harness coiled EOF for customer installed remote throttle and remote PTO controls. Harness includes Remote PTO control and Remote Throttle controls. T680/T880 models do not require 12-way engine connector sales codes. All other models require (1900082 or 1900084).	2

Transmission & Clutch

2011205	O	Transmission: Allison 3000RDS 6-speed w/PTO drive gear. 5th Gen controls. Includes heat exchanger & oil level sensor. Rugged Duty Series for vocational applications. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions. Requires a push button shift control code. Oil temperature gauge is standard on class 8 models.	291
2401405	O	Driveline: 2 Dana standard-duty; 1 centerbearing. *Standard duty is 1710 series.	77
2409916	O	One bolted centerbearing crossmember. This option upgrades an existing crossmember. The cost does not include the centerbearing and bracket. Crossmember location will be in accordance with Kenworth engineering standards, using the major components specified on the DTPO.	11
2410018	O	Torque converter included w/Allison Transmission.	0
2410204	O	Delete Allison Fuel Sense	0
2410244	O	J1939 Park Brake Auto Neutral	0
2429358	O	Rear transmission support springs for transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	0

Front Axle & Equipment

2506181	O	Dana Spicer D2000 Front Axle rated 20K standard track.	120
2603006	S	Front brakes included w/ front hub package.	0
2703211	O	Front Brake:Bendix 16.5x6 air brake package For 18K/20K non-driving front axle. Includes cast drum, 10 bolt iron Preset hub piloted hub, hubcap & slack adjusters.	113
2866008	O	Front Springs: taperleaf, 20K 2-stage with shocks and 54 in. spring length. T370 with 20K front axle only.	172
2895305	O	Dual power steering gear: 18/20K	77
2899336	O	Power Steering Cooler:Radiator Mounted Air-to-Oil	11

Rear Axle & Equipment

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/3/2019 12:56:00 PM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q00099293
Prepared by:	ID: mkilgor		Version Number:	41.20



Data	Code	Description	Weight
3124403	O	Dual Dana Spicer DSP41 rear axle rated at 40K. (DSP40 w/ heavy-wall housing) w/ 11mm housing and 1.88in. shaft diameter. Tandem rear axles.	2,126
3200557	O	Rear Axle Ratio - 5.57.	0
3300002	O	Dual rear brakes included w/rear hub package.	0
3401002	O	Dual 46K Air Brake package includes 16-1/2x7 in. brakes, cast drums, aluminum 10-bolt hub pilot Preset hubs, slack adjusters and oil seals for use w/ 22.5 in. wheels.	0
3485207	O	Spring Brake: 3030 long stroke dual 30 square inches travel; replaces standard 2-1/2 in. travel. Helps keep brakes in adjustment longer.	4
3490047	O	Dustshields for drum brakes: all rear axles.	11
3495226	S	Bendix 4S/4M anti-lock brake system.	0
3500037	O	Interaxle driveline:1 Dana 1710 Series	0
3532125	O	Wheel Differential Lock for Dana Spicer axles DSP40/DSP41(P)/DSH40(P)/DSH44(P)/D40-155 rear rear axle. Under Speed Interlock is standard on T680.	15
3730028	O	Rear suspension: Tandem Kenworth Airslide 400L 40K. 52 in. axle spacing. Air suspension w/ 8.5 in. ride height. Includes single leveling valve. Includes air suspension dump valve.	258

Tires & Wheels

4038678	O	Front tires: Goodyear G289 WHA 315/80R22.5 20PR. All position. 43.1 in. diameter. 20 in. SLR.	78
4238681	O	Rear tires: Goodyear G182 RSD11R22.5 14PR 42.1 in. diameter, all position. 19.6 in. SLR. Code is priced per pair of tires.	104
4900008	O	Rear Tire Quantity: 8	0
5045280	O	Front Wheel: Alcoa 89U64 22.5X9 AL Ultra ONE Wheel.	-24
5245271	O	Rear Wheel: Alcoa 88367/Accuride 51487 22.5x8.25, aluminum outside with Lvl One[™] finish/steel Steel Armor [™] powder coat inside, hub-pilot mount. 7400 lb. maximum rating. Includes wheel guards. Air disc brake compatible. Code is priced per pair of wheels.	-80
5853906	O	Powder coat white steel wheel. Use in conjunction with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	0
5854010	O	Single Front Axle: 2 Polished wheels. Polished outboard surface of aluminum wheels.	0
5900008	O	Rear Wheel/Rim Quantity: 8	0

Frame & Equipment

**Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	1/3/2019 12:56:00 PM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q00099293
Prepared by:	ID: mkilgor		Version Number:	41.20



Data	Code	Description	Weight
6056600	O	Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel 337in. to 416 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	612
6308715	O	Bumper: Aerodynamic Chrome Requires a bumper setting code.	0
6319409	S	40.9 in. Bumper setting. Requires a bumper code.	0
6321005	O	Removable Front Tow Hooks: 2.	15
6390103	S	Front mudflaps.	0
6400636	O	Battery box cantilever aluminum BOC with fiberglass cover. N64000 please use NPO code 6409902 N64010 RH BOC battery box, ref vin N64020 482682 past build that this N64030 was put on.	0
6409901	O	Battery box location: LH Side.	0
6451059	O	T270/370 Non-polished 2010 or later DPF/SCR cover with cab access step assembly, RH under. End plates will be painted standard black frame color.	0
6490124	O	Five-piece bolted crossmember assembly with 16mm frame fasteners, center and rear frame.	-32
6490427	O	Aluminum underbell crossmember. Only with non-drive front axle 16K and greater. For T370 only.	19
6490430	O	Bolted Rear Cab Support Crossmember. Replaces T3 standard.	17
6741023	O	Square end-of-frame w/ bolted crossmember, non-towing.	41

Fuel Tanks & Equip

7210056	O	Fuel Tank: 56 US gallon 24.5in. aluminum under replace.	-45
7722011	O	Small round DEF tank. 11 gallons of usable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0
7889203	O	Standard DEF to fuel fill ratio: 2:1 or greater.	0
7889245	O	Anti-siphon device swaged in place. For any number of fuel tanks.	1
7889604	O	DEF tank location is on the LH.	0
7920056	O	Location: 56 gal fuel tank LH under cab	0

**Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	1/3/2019 12:56:00 PM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q00099293
Prepared by:	ID: mkilgor		Version Number:	41.20



Data	Code	Description	Weight
Cab & Equipment			
8024310	S	Cab: Curved Glass Conventional. Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection, short and open check diagnostics. Warning alarm will sound when lights are left on.	0
8080137	O	Cab door bearing blocks, top & bottom.	0
8090310	S	Hood: Sloped aerodynamic hood includes grill & separate bumper.	0
8108010	S	Cab heater: W/integral defrosters & A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.	0
8201200	O	Adjustable telescoping tilt steering column.	10
8221105	O	Gauge: Air application gauge.	0
8282009	S	Instrument package: Includes speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	0
8330003	S	Cab interior: Pinnacle. Includes vinyl headliner & cab back panel, slate gray interior, dark slate gray seats, floor mats, LH/RH inside sunvisor & door courtesy lights.	0
8410191	O	Driver seat: Kenworth Air cushion Plus HB vinyl. Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6-23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted and includes a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	2
8480180	O	Rider seat: Kenworth Toolbox Plus IB vinyl. W/dual armrests.	-4
8601421	O	Kenworth Radio with AM/FM/WB/USB and Bluetooth	4
8700083	O	Under-dash center console: W/2 cup holders, 1 ashtray, 1 lighter, 1 12V outlet & a storage compartment.	0
8700154	O	Self cancelling turn signal: W/head light dimmer switch .	0
8800200	S	Cab access contoured grabhandles, LH/RH.	0
8832115	O	Daylite Door: LH/RH includes RH peeper window	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/3/2019 12:56:00 PM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q00099293
Prepared by:	ID: mkilgor		Version Number:	41.20



Data	Code	Description	Weight
8841303	O	Single Rectangular Air Horn 23 in. LH Top of Roof Includes Air Horn Cover.	6
8850210	S	Dual convex mirrors 7-1/2 in. w/ offset mounting, and non-heated.	0
8850300	S	Look-Down, Pass. Door, Stainless 8.5x4.4	0
8866101	O	Mirror: Dual Prutsman mirror 7 in. x 16 in. polished stainless steel, thermostatically controlled. switch located on door pad.	0
8869005	S	Mirror brackets 8-1/2 ft load width.	0
8871438	S	Rear Cab Stationary Window 17 in. x 36 in.	0
8879200	S	Manual LH & electric-powered RH door window. Switch located on door.	0
8890135	O	Exterior stainless steel sunvisor.	11

Lights & Instruments

9010801	S	Headlamps: Halogen Projector Low Beam, Halogen Complex Reflector High Beam	0
9022135	O	Marker Lights: Five rectangular.	0
9030010	S	Turn Signal Lights: Mounted on fender	0
9070138	S	Combination Stop, Tail, Turn & Backup Lights RH & LH.	0
9090115	O	Reflectors: Two Midframe	0
9090845	O	Circuit Breakers: Replacing fuses. Does not apply to any 5-amp fuse box position. Brakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat, gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.	0

Air Equipment

9101023	O	Air dryer: Bendix AD-SP heated. With 2010 engine installations the dryer is mounted under the hood.	0
---------	---	---	---

Extended Warranty

9200008	O	Base Warranty - PACCAR PX-9 Engine 24 months / 250,000 miles / 402,336 km / 6250 hours.	0
9200022	S	Base Warranty - Standard Service Medium Duty 12 months / Unlimited miles & km	0

Miscellaneous

9400072	O	Ship to Dealer.	0
9409852	O	GHG Secondary Manufacturer: Does Not Apply	0

Promotions

9502071	U	Matt Kilgore	0
---------	---	---------------------	---

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/3/2019 12:56:00 PM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q00099293
Prepared by:	ID: mkilgor		Version Number:	41.20



Data	Code	Description	Weight
Paint			
9700000	O	Paint color number(s). N97020 A - L0006 WHITE N97200 FRAME N0001 BLACK	0
9943004	O	Bumper Unpainted	0
9943050	O	Day Cab Standard Paint	0
9944820	O	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
9965510	S	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0
Total Weight			14495 lb

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/3/2019 12:56:00 PM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q00099293
Prepared by:	ID: mkilgor		Version Number:	41.20