



827 S 7th St  
Kansas City, KS 66105  
Main Tel. (833) 653-8100

## Specification #5719, Reference M2 4K VAC

<b>Customer</b>	Stock Vacuum	<b>Job #</b>	<b>4678</b>
<b>Reference</b>	M2 4K VAC	<b>Date</b>	18-Feb-2021

ITEM	DESCRIPTION	QTY
CHASSIS-FLOWMARK SUPPLIED	<b>Chassis</b> - 2020 Freightliner M2, 350hp Cummins, Allison, see specs	1
IV-AL-40	<b>4000 US Gallons Aluminum Vacuum Tank</b> - 4000 total US gallons - single compartment tank - 1/4" barrel - 3/8" heads - reinforced sills with composite isolation boards - 12" primary shut off with 3" plumbing - 20" top manway - 20" rear cleanout - steps at top manway - full head anti-surge baffles - interior ring stiffeners as required - full length aluminum hose trays with diamond plate protector - 4" rear load line with 4" TTMA flange and stainless deflector - 6" discharge with 6" TTMA flange - (2) rear hose hooks - (3) 5" site eyes - LED light kit with S/T/T, (2) work lights, clearance and DOT triple lights - 10 year, no-leak tank warranty	1
IV-PU-4310BELT	<b>Vacuum Pump</b> - NVE4310 MaxPak - air cooled, 940 cfm blower - Soft start PTO fro automatic transmissions - frame mount NVE secondary - frame mount NVE exhaust silencer - frame mount NVE ballast filter - driveshaft, belt drive - fully enclosed blower package - includes 4in brass lever valve, adapter and dust cap on inlet - includes 6in brass lever valve, adapter and dust cap on discharge - standard pumper bumper	1
IV-PU-HOTSHIFT	<b>PTO Option</b> - hot-shift PTO (required for auto trans) - soft start PTO for blower - in-cab control	1
IV-OPTION-36CAB	<b>Toolbox</b> - 36" frame mount toolbox - double barn door, smooth aluminum	1