

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
Base Chassis, Model CV515 SFA with 165.00 Wheelbase, 83.80 CA, and 63.00 Axle to Frame.	4671/2886	7557

AXLE CONFIGURATION

AXLE CONFIGURATION {Navistar} 4x2	0/0	0
-----------------------------------	-----	---

Notes

: Pricing may change if axle configuration is changed.

ENGINE

ENGINE, DIESEL {International 6.6} EPA 2017, 350HP @ 2700 RPM, 700 lb-ft Torque @ 1600 RPM, 2900 RPM Governed Speed, 350 Peak HP (Max)	0/0	0
--	-----	---

Includes

: OIL FILTER, ENGINE Spin-On Type

RADIATOR Aluminum, 3-Row, Down Flow, Front to Back System, 730 SqIn Louvered, with 578 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler	0/0	0
--	-----	---

FAN DRIVE Viscous Type, Screw On, Rear Tether, Electronically Controlled	0/0	0
--	-----	---

AIR CLEANER Single Element, with Water Separator	0/0	0
--	-----	---

BLOCK HEATER, ENGINE 120V/800W	0/0	0
--------------------------------	-----	---

EMISSION COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal located on Driver Door	0/0	0
---	-----	---

FEDERAL EMISSIONS {International 6.6} EPA, OBD and GHG Certified for Calendar Year 2019	0/0	0
---	-----	---

GOVERNOR Electronic Road Speed Type; with 75 MPH Default	0/0	0
--	-----	---

THROTTLE, HAND CONTROL Engine Speed Control for PTO; Electronic Controlled, On/Off Switch Mounted on Dash, with Steering Wheel Button Control	0/0	0
---	-----	---

TRANSMISSION

TRANSMISSION, AUTOMATIC {Allison 1700 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Park Pawl, with 19,500-lb GVW and 26,000-lb GCW Max, On/Off Highway	0/0	0
---	-----	---

PTO LOCATION Customer Intends to Install PTO at Right Side of Transmission	0/0	0
--	-----	---

SHIFT CONTROL PARAMETERS {Allison} 1000 or 2000 Series Transmissions, Performance Programming	0/0	0
---	-----	---

REAR AXLES, SUSPENSIONS

AXLE, REAR, SINGLE {Dana Spicer S14-110} Single Reduction, 13,500-lb Capacity, 190 Wheel Ends . Gear Ratio: 4.30	0/0	0
--	-----	---

SUSPENSION, REAR, SINGLE 13,500-lb Capacity, Vari-Rate Springs	0/60	60
--	------	----

DIFFERENTIAL, LOCKING {Dana Spicer Truetrac} Torque Proportioning Limited Slip	0/0	0
--	-----	---

Notes

: Axle Lead Time is 90 Days

SHOCK ABSORBERS, REAR (2)	0/50	50
---------------------------	------	----

FRONT AXLES

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
AXLE, FRONT NON-DRIVING {Dana Spicer D-800N} I-Beam Type, 6,000-lb Capacity	0/0	0
FRONT SUSPENSIONS		
SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 6,000-lb Capacity, with Shock Absorbers	0/0	0
CABS, COWLS, BODIES		
CAB Conventional, Day Cab	0/0	0
<u>Includes</u>		
: DOME LIGHT, CAB with OFF/DOOR/ON Settings; Located in Overhead Console		
: READING LIGHT, CAB Located in Overhead Console		
: STEP (2) One Per Door		
: STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door		
AIR BAG, FRONT, DRIVER SIDE	0/0	0
AIR BAG, FRONT, PASSENGER SIDE	0/0	0
AIR BAG, SIDE, DRIVER Seat Mounted, Outboard Side-Impact Airbag	0/0	0
AIR BAG, SIDE, PASSENGER Does not have side air bag	0/0	0
AIR BAG, SIDE CURTAIN Roof Mounted, for Front and Rear Outboard Seating Positions for Driver and Passenger Sides	0/0	0
AIR CONDITIONER with Heater, Single Zone	0/0	0
CAB INTERIOR TRIM Diamond, for Day Cab	0/0	0
COLOR, INTERIOR Dark Ash	0/0	0
DOOR HANDLE, EXTERIOR Bright Finish	0/0	0
GAUGE CLUSTER English Speedometer, Includes English Odometer; Includes 4.2" Color Display with Personalization, Warning Messages and Vehicle Information	0/0	0
GLASS, ALL WINDOWS Solar Absorbing, Tint	0/0	0
KEYLESS ENTRY SYSTEM REMOTE with Panic Alarm and Horn Beep Lock Confirmation, Includes Two Key Fob Transmitters	0/0	0
MIRROR, INSIDE REAR VIEW with Automatic Dimming	0/0	0
MIRRORS (2) Manual Folding and Extending, Power Adjust, Heated, Turn Signal Indicator Located in Mirror, Black Heads and Arms, for 96" Load Width	0/0	0
SEAT, DRIVER High Back with Integral Headrest, 10-Way Power Adjustable, Cloth, Manual Adjust Lumbar	0/0	0
SEAT, TWO-MAN PASSENGER High Back with Integral Headrest in Outboard Position, Center Fold-Down Armrest with Storage, Lockable Storage in Seat Cushion, Cloth, with Recline	0/0	0
SUN VISOR, INTERIOR with Illuminated Mirror for Driver and Passenger Sides	0/0	0
WINDOW, POWER (2) in Left and Right Doors	0/0	0
FRAMES		
FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield), Straight Top Flange with Contoured Bottom, Height Transitions from 7.375" (187.325mm) to 9.125" (231.775mm) to 7.625" (193.675mm); Width: 3.079" (78.21mm); Thickness: 0.3125" (7.94mm); 383.3" (9735.8mm) Max OAL	28/78	106

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
BUMPER, FRONT Contoured, Steel, Chrome Plated, for CV and RE Bus	0/0	0
TOW HOOK, FRONT (2) Frame Mounted	13/-1	12
LICENSE PLATE HOLDER Includes Upper & Lower Mounting Plate Hardware, Mounted in Existing Holes in Front Bumper	2/0	2
WHEELBASE RANGE 128" (325cm) Through and Including 183" (465cm)	0/0	0
BRAKES		
BRAKE SYSTEM, HYDRAULIC {Bosch} Split System, with Four Channel ABS, Traction Control, Hydromax Brake Booster and Master Cylinder	0/0	0
BRAKES, FRONT, HYDRAULIC DISC Quadraulic; Four 64mm Diameter Pistons	0/0	0
BRAKES, REAR, HYDRAULIC DISC Quadraulic; Four 64mm Diameter Pistons	0/0	0
BRAKE, PARKING {Bosch} DSSA Type, 12" x 3"; for Hydraulic Brake Chassis; Foot Operated in Cab; Differential Mounted	0/0	0
DUST SHIELDS, FRONT BRAKE for Hydraulic Brakes	0/0	0
DUST SHIELDS, REAR BRAKE for Hydraulic Brakes	0/0	0
STEERING		
STEERING GEAR {Bosch S2 8014 Plus} Power	0/0	0
STEERING COLUMN Tilting	0/0	0
STEERING WHEEL 4-Spoke; 15" Dia., Black, Leather Wrapped	0/0	0
DRIVELINES		
DRIVELINE SYSTEM {Dana Spicer} SPL100, for 4x2/6x2	12/35	47
EXHAUST SYSTEMS		
EXHAUST SYSTEM Horizontal, Frame Mounted Right Side, Under Rail, for Single Exhaust	0/0	0
ENGINE EXHAUST BRAKE for International 6.6 Engine	0/0	0
MANUAL REGEN Capability, Omit	0/0	0
ELECTRICAL SYSTEMS		
ELECTRICAL SYSTEM 12-Volt for CV Model	0/0	0
<u>Includes</u>		
: HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover		
: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever		
: PARKING LIGHT PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light		
: TURN SIGNAL SWITCH Self-Cancelling with Lane Change Feature		
: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature, Integral with Turn Signal Lever		
ALTERNATOR {Denso SC6} Brush Type, 12 Volt, 220 Amp Capacity	4/0	4
BATTERY BOX Steel, with Plastic Cover, 2 Battery Capacity, Parallel to Rail, 28" Wide, Mounted Left Side Under Cab	0/0	0
BATTERY SYSTEM {VARTA} Maintenance-Free, (2) 12-Volt 1100CCA Total, Top Threaded Stud	0/0	0

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Crew Cab at Left Frame; Includes One Sealed Connector for Separate Ground/Backup/Left and Right Hand Turn, Left and Right Hand Tail/Stop/Accessory Power and Combined for Left and Right Hand Stop/Turn	3/1	4
CLEARANCE/MARKER LIGHTS (5) Amber LED Lights, Flush Mounted on Cab	0/0	0
COMPACT DISC PLAYER with MP3	2/0	2
HEADLIGHTS Halogen, Composite Aero Design, Black Trim Bezel, with Daytime Running Lights	0/0	0
HORN, ELECTRIC Disc Style	0/0	0
RADIO AM/FM/Bluetooth/USB Input/Auxiliary Input/SD Card Slot, with 8" Color Touch Panel Display, Voice Activated Technology, Satellite Radio Compatible	0/0	0
SPEAKERS (6)	2/0	2
STARTING MOTOR 12 Volt	0/0	0
STOP, TURN, TAIL & B/U LIGHTS Multi-Function, Sealed, Incandescent Stop, Turn and Tail Lights, Backup Lights with Rear Reflex Reflector, Includes License Plate Light	0/0	0
SWITCH, AUXILIARY 1 to 4 Latching Switches with 30-Amp Fuses	0/0	0
TRAILER BRAKE CONTROL Integrated	6/13	19
TRAILER CONNECTION SOCKET Mounted at Rear of Frame, Wired for Turn Signals Combined with Stop, Compatible with Trailers with Combined Stop, Tail, Turn Lamps	8/-2	6
FRONT END		
FRONT END Tilting, Fiberglass, with Three Piece Construction	0/0	0
BUG SCREEN No	0/0	0
FENDER EXTENSIONS Molded in Black	0/0	0
GRILLE Molded in Dark Gray	0/0	0
LOGOS EXTERIOR Model Badges	0/0	0
SPEEDOMETER, TOOLS, MISC		
PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
GVWR WEIGHT CLASSIFICATION Class 5 (16,001-19,500 lbs)	0/0	0
FUEL TANKS		
FUEL TANK Top Draw, Plastic, Rectangular, 17" Tank Depth, 40 US Gal (151L), Includes Auxiliary Draw Port and Fuel Filler Assembly, Mounted Between Frame Rails and Behind Rear Axle	0/0	0
DEF TANK 6.75 US Gal (26L) Capacity, Frame Mounted Outside Right Rail, Under Cab	0/0	0
WHEELS, TIRES - FRONT		
WHEELS, FRONT {Accuride 29695} DISC; 19.5x6.75 Rims, Extra Polish Aluminum, 8-Stud, 275mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/0	0
(2) TIRE, FRONT 225/70R19.5 Load Range G HYBRID HS3 (CONTINENTAL), 649 rev/mile, 87 MPH, All-Position	-10/0	-10

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
WHEELS, TIRES - REAR		
WHEELS, REAR {Accuride 29695} DUAL DISC; 19.5x6.75 Rims, Extra Polish Aluminum Outer Wheel, Steel Inner Wheel, 8-Stud (275MM BC) Hub Piloted, Flanged Nut, Metric Mount, with Steel Hubs	0/0	0
(4) TIRE, REAR 225/70R19.5 Load Range G HDR (CONTINENTAL), 647 rev/mile, 87 MPH, Drive	0/-20	-20
WHEELS, SPARE		
WHEEL, SPARE, DISC {Accuride 29695} 19.5x6.75 Rims, Extra Polish Aluminum, 8-Stud, 275mm BC, Hub-Piloted	0/0	0
Cab schematic 100CX		
Location 1: 9219, Winter White (Std)		
Chassis schematic N/A		
Services Section:		
WARRANTY		
WARRANTY Standard for CV515, Effective with Vehicles Built December 3, 2018 or Later, CTS-3000A	0/0	0
Total Component Weight:	4741/3100	7841
Set parameters	0/0	0
Total Goods Purchased:	0/0	0

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.